Trilogy: Narrow Stile Access Locks

DL1200, DL1300, PDL1300 PIN and PIN/prox aluminum door retrofit outside trim



- Aluminum door retrofit outside trim for Adams Rite[®] 1850, 1950, 4710, 4070, 4730, 4900 Series and MS1850S and MS1950S Series latch locks.
- Field-proven, familiar Trilogy[®] programming & electronics
- PIN code and PIN/Prox Models support 100 to 2000 users (see model info.)
- **40,000 event audit trail** in 1300 Series models, provides door usage activity reports at wireless handheld printer, laptop or PC.
- All-metal, vandal-resistant 12-button keypad supports 3-6 digit PIN codes, and multilevel user hierarchy (master, manager, supervisor, basic users)
- Keypad or PC programmable (see model info.). Quickly and easily add or delete users and enter "passage mode", service codes, group lock-out & group-enable
- HID Prox ID cards, keyfobs and prox tags supported in PDL-1300 Series models featuring built in Prox reader. (High security applications can require use of both PIN code plus Prox ID for access.)
- **Real time clock and PC programmable automatic lock/unlock scheduling** for 500 events (1300 Series models).
- Wide weatherproof operating range from -31 to 151°F (-35 to 66C)
- Wireless standalone locks: Long-life, battery- operated; Includes audible and visual low battery alert. (Uses standard off-the-shelf batteries.)
- Non-handed; fully field-reversible
- Key override; interchangeable cores supported (Corbin/Russwin, Yale, Schlage, Medeco.)
- Mortise Cylinder, 1-1/4" supplied. (Supports 1-1/8, 1-1/4 and 1-3/8")
- Compact styling 14-3/8"H x 1-5/8"D x 1-3/4"W
- Backsets 31/32",1-1/8" and 1-1/2" ; Stile thickness 1-3/4"
- Four attractive standard finishes US26D Satin Chrome, US10B Duronodic, MS Metallic Silver and MB Metallic Bronze

Narrow Stile Trilogy[®] Lock models:

- DL1200 Series supports 100 users, fingertip/keypad programmable. (Includes 2 Lithium 3V batteries).
- **DL1300 Series** supports 2000 users and includes 40,000 event audit trail and 500 event schedule. Keypad or PC programmable. (Includes 2 Lithium 3V batteries) (See accessories below.)
- PDL1300 Series supports 2000 PIN or Prox users and includes 40,000 event audit trail and 500 event schedule. Keypad or PC programmable. (Includes 2 Lithium 3V batteries) (See accessories below.)
- KIT ALSO AVAILABLE: Complete electronic and mechanical access retrofit kit including Trilogy electronic narrow stile trim and mechanical Adams Rite 4900 Series dead latch lock (specify either 1 1/8" or 1 1/2" backset for mechanical lock required).



ORDERING: DL1200/26D1

Model T	уре ———	
PDL – Pr	ox/PIN	
DL – Dig	ital PIN	
Trilogy S	eries ——	
12 – 270	0 Series	
13 – 300	0 Series	
Trim —		
00 = Lev		
25 = Turi		
50 = Kno		
75 = Reg	jal lever	
Finish —		
	in Chrome	
/10B Dur		
/MS Met	allic Silver	(III) CC
/MB Met	allic Bronze	Celle

Mechanical Dead Latch

- 1 Supports Adams Rite: 4710, 4730, 4900 Series
- 2 Supports Adams Rite:
- 4070, MS1850S, MS1850S-050, MS1950,
- MS1950-050 3 – KIT Includes Adams Rite 4900 with
- 1-1/8" backset, 628 &313 faceplate 4 – KIT Includes Adams Rite 4900 with
- 1-1/2" backset, 628 & 313 faceplate





hospitals schools airports Trilogy 1200 & 1300 Series: Convenient Keyless Access and Audit Trail anywhere there's an aluminum narrow stile door:
 Storefronts Managed Properties Restaurants Retail Airports Showrooms Campuses Hospitals Businesses Strip Malls
retail pharmacies offices

Trilogy audit trail lock accessories for 1300 Series



AL-DTMII Data Transfer Module used to transfer program data from the PC (running DL-WINDOWS software) to the lock and receives audit trail from the lock. Can store data for up to 96 locks at a time.



AL-PCI2 Trilogy PC Software Kit Windows-format software kit

used to program Trilogy lock, codes, schedules, view audit trail reports. Kit includes DL-WINDOWS software and (required) computer interface cable for use on serial port. Note: Requires DL-WINDOWS Software version 3.04 or higher.

AL-PCI2-USB , As above, but with interface cable for USB port.

DL-WINDOWS Upgrade for Trilogy software version (software only). (Contained in two items above.)



AL-PRE: Prox Card Reader/Enroller Enables instant, automatic enrollment of Prox cards, keyfobs, tags into DL-Windows (Simply present the prox Card/fob device to the unit's faceplate to enroll—no need to be in the presence of the lock while enrolling-eliminates the need for keyboarding each badge's number).

Supports all Prox cards, keyfobs and tags. Simultaneous card enrollment, downloading or uploading – all on just one serial port. 9V Battery operation.

AL-IR1 Infrared Printer (right) Prints the event log and user code with wireless hand-held convenience (battery operated).



There's a Trilogy keyless access lock for every requirement and application

		-			-				
MODEL:	DL12/1300	DL2700	DL2800	DL3000	DL4100	DL3500	DL4500	ETDL	DK3000
Lock Type	Narrow stile	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Mortise	Mortise	For Panic Trim	Keypad
Prox Reader model	PDL1300			PDL3000	PDL4100	PDL3500	PDL4500	ETPDL	PDK3000
Users	100 - 2000	17	200	DL3000 300; PDL3000 2000	2000	DL3500 300; PDL3500 2000	2000	2000	2000
Audit Trail	0 - 40000		1000	1600; 40000 (PDL)	40000	40000	40000	40000	40000
Schedules	0 - 500		150	150; 500 (PDL)	500	500	500	500	500
Privacy function					Yes		Yes		
Classroom/ Deadbolt						CR or DB	DB		
Weather proof -31 to 151ºF	Standard	WP version	Standard	WP version	Standard	Standard	Standard	Standard	Standard
Handing	Non	Non	Non	Non	Non	Field Reversible	Field Reversible	Non	
Std. Door Thickness	1-3/4"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	1-5/8 to 1-7/8"	
Std. Backset	31/32", 1-1/8" 1-1/2"	2-3/4"	2-3/4"	2-3/4"	2-3/4"	2-3/4"	2-3/4"		
Cylinder or IC Prep	mortise, incdd	key in knob or 9 ICs	key in knob or 9 ICs	key in knob or 9 ICs	key in knob or 9 ICs	mortise, incdd	mortise, incdd	rim cyl., incdd	
Finishes (US)	26D, 10B, MS, MB	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26, 26D, 3, 5, 10B	26/D, 3, 5, 10B, MS, MB

